

TECHNICAL SPECIFICATIONS

SPECIFICATIONS	
IP Cameras	<ul style="list-style-type: none"> Up to 16 IP cameras can be connected to the DVS IP Camera support for leading manufacturers (Contact Systems With Intelligence for the latest list of supported IP Cameras) H.264 video streaming Resolution and frame rate dependant on IP camera used HD and megapixel images supported ONVIF IP Camera Support
Video Output	<ul style="list-style-type: none"> 1 VGA interface for computer monitor
USB	<ul style="list-style-type: none"> 4 USB Ports
Storage	<ul style="list-style-type: none"> Up to 2TB using solid state drives
LAN Interface	<ul style="list-style-type: none"> Included: 1-port 10/100/1000TX RJ45 Interface Optional: 2-ports 10/100/1000TX RJ45 or 100FX Fiber Interface
Optional Modules	<ul style="list-style-type: none"> Serial Interfaces: 4 x RS232/RS422/RS485 DB9 modules Serial Interfaces: 8 x RS232/RS422/RS485 RJ45 modules Wireless: 802.11 b/g*, Cellular Modem*
Power Supply	<ul style="list-style-type: none"> 24VDC, 48VDC, 105 -300VDC or 85-250VAC; Optional dual redundant power supplies
Operating Temperature	<ul style="list-style-type: none"> -40 °C to +85 °C; no cooling fans
EMC/EMI	<ul style="list-style-type: none"> IEC 61850-3; IEEE 1613; IEC 61000-6-2; IEC 61800-3
Mounting/Dimensions	<ul style="list-style-type: none"> 19" Rack Mount; 2U height
Warranty	<ul style="list-style-type: none"> 2 Years

* Future option available soon.

DIMENSIONS Unit: inches (mm)

